

VS-600

Vital Signs Monitor



Physical Specifications

Weight	1.9 kg (with SpO ₂ , NIBP and a battery) 1.7 kg (with NIBP and a battery)
Size	134 mm � 120 mm � 243 mm
Screen type	Segment display
Screen size	90mm � 90mm

EMC Compliance Meets the requirements of IEC 60601-1-2.

Classifications

Defibrillation proof (protection against electrical shock)	Type CF: SpO ₂ , NIBP and Temp
Water proof	IPX1
Degree of mobility	Portable

Patient Type Adult, Pediatric, Neonatal

NIBP

Meet standards of IEC 80601-2-30, ISO 81060-2.	
Technique	Oscillometry
Operation mode	Manual
Parameters	Systolic, diastolic, mean, Heart Rate
Max Measure time	Adult/Pediatric: 180 s, Neonate: 90 s
Systolic range	Adult: 40 to 270 mmHg Pediatric: 40 to 200 mmHg Neonate: 40 to 135 mmHg
Diastolic range	Adult: 10 to 210 mmHg Pediatric: 10 to 150 mmHg Neonate: 10 to 100 mmHg
Mean range	Adult: 20 to 230 mmHg Pediatric: 20 to 165 mmHg Neonate: 20 to 110 mmHg
NIBP accuracy	Max mean error: � 5 mmHg Max standard deviation: 8 mmHg
NIBP resolution	1 mmHg

Mindray SpO₂

Meet standards of ISO 80601-2-61.	
SpO ₂ range	0 to 100 %
SpO ₂ resolution	1%
SpO ₂ accuracy	70 to 100%: �2% (without motion in adult /pediatric mode) 70 to 100%: �3% (without motion in neonate mode) 0% to 69%: Not specified.
Perfusion indicator (PI)	Yes, for Mindray SpO ₂

Masimo SpO₂

Meet standards of ISO 80601-2-61.	
SpO ₂ range	1 to 100 %
SpO ₂ resolution	1%
SpO ₂ accuracy	70 to 100%: �2% (without motion in adult /pediatric mode) 70 to 100%: �3% (without motion in neonate mode) 70 to 100%: �3% (measured with motion) 1% to 69%: Not specified.
Perfusion indicator (PI)	Yes, for Masimo SpO ₂

Nellcor SpO₂

Meet standards of ISO 80601-2-61.	
SpO ₂ range	0 to 100 %
SpO ₂ resolution	1%
SpO ₂ accuracy	70 to 100%: �2% (adult/pediatric) 70 to 100%: �3% (neonate) 0% to 69%: Not specified.
Perfusion indicator (PI)	No

PR from Mindray SpO₂

PR range	20 to 254 bpm
PR accuracy	� 3 bpm (without motion)

PR from Masimo SpO₂

PR range	25 to 240 bpm
PR accuracy	w 3 bpm (without motion) w 5 bpm (with motion)

PR from Nellcor SpO₂

PR range	20 to 300 bpm
PR accuracy	�3 bpm (20 to 250 bpm) Not specified (251 to 300 bpm)

PR from NIBP

PR range	40 to 240 bpm
PR accuracy	w 3 bpm or �3%, whichever is greater

SmarTemp� Temperature

Meet standard of ISO 80601-2-56.	
Technique	Thermal resistance
Operating mode	Adjusted mode (predictive mode) Direct mode (monitor mode)
Measurement range	Monitor mode: 25 �C to 44 �C (77 �F to 111.2 �F) Predictive mode: 35 �C to 43 �C (95 �F to 109.4 �F)

Accuracy (Monitor mode)	25 �C to 32 �C (not include 32 �C); 32 �C to 44 �C (include 32 �C); � or 77�F to 89.6�F (not include 89.6�F 89.6�F to 111.2�F (include 89.6 �F)
Resolution	w 0.1 �C or � 0.2 �F

Indicator

LED indicator	Power on LED (1), two color: yellow/green AC power LED (1), green Battery LED (1), green
Audible indicator	Give pulse tone, power-on self check tone
Other	Technical alert on screen

Interfacing

Main unit	AC power connector (1) RS 232 connector (1), for DIAP protocol
-----------	---

Power

AC line voltage	100 to 240 VAC (�10 %)
AC frequency	50/60 Hz (�3 Hz)

AC current 0.9 to 0.5 A
Battery type Rechargeable lithium-ion battery,
Battery run time At least 11 hours (2600mAh battery)
At least 22 hours (4500mAh battery)

Relative humidity Operating: 15 to 95 % (non condensing)
Storage: 10 to 95 % (non condensing)
Barometric Operating: 57.0 to 107.4 kPa
Storage: 16.0 to 107.4 kPa

Environmental Requirements

Temperature Operating: 0 to 40 °C (without Temp)
5 to 40 °C (with Temp)
Storage: -20 to 60 °C

Some of functions marked with an asterisk may not be available.
Please contact your local Mindray sales representative for the most
current information.

www.mindray.com

P/N:ENG-VS-600 Datasheet -210285X2P-20190529
�2019 Shenzhen Mindray Bio-Medical Electronics Co., Ltd. All rights reserved.

